


SlimFix® is a high strength low-profile system with fast response, and is ideal for renovation, new build, whole house or single room projects. SlimFix® is available in 18mm or 25mm thickness boards.

The system is designed for wood and laminate floors, or carpets and vinyls with a suitable cover board such as our DriDEK™-20 board (this solution has excellent acoustic characteristics).



### Technical:

- Material: XPS-500
- Dimensions: 1200mm x 600mm
- Thickness: 18mm or 25mm
- Pipe centres: 100mm or 150mm
- Pipe channels: 12mm or 16mm
- Compressive strength: 500kPa
- Panel weight: 0.5kg or 0.7kg
- Edge profile: square edge
- Foil diffuser: 200µm
- Continuous service temperature limit: 75°C
- Thermal conductivity: 0.034W/mK

### Other properties:



- Global warming potential: <5
- Ozone depletion potential: 0
- BRE Green Guide rating: A
- Fire protection class: E
- 100% recyclable
- Non-toxic and non-biodegradable
- Raw material manufactured in accordance with BS EN 13164

### Features:

- Suitable for any floor construction
- High-performance system, suitable for all heat sources
- One universal panel, no need for end return panels
- Pipe centre variants to optimise design requirements

### SlimFix® options:

- SlimFix®-18 Ultra uses SUPERflex™-12 pipe at 100mm or 150mm centres
- SlimFix®-25 Ultra uses AluPlas® or SUPERflex™-16 pipe at 150mm centres



### About us

No ifs, no buts. The award-winning Continal® service means you get an underfloor heating system delivered to you on time, on site, every time, no compromise.