



Continal
UNDERFLOOR HEATING

UltraSlim™-15 panel system

UltraSlim™-15 – Our lowest profile system at just 15mm thin. Fast response, suitable for all heat sources and is ideal for renovation and new build.

UltraSlim™-15 combines a high strength MDF base, and heat dissipation layer to maximize output and temperature variance

The universal UltraSlim™-15 panels provide pipe routing for return loops and distribution, providing simple installation.

Key system characteristics:


- Floating floor system suitable for any floor construction
- 15mm panel
- High output emissive composite panel for maximum performance
- Low profile system
- Quick response
- High performance system suitable for all heat sources
- Universal panel for simple installation
- Pipe centre variants to optimize design requirements

For:

- Ultra-low profile build up
- Renovation or new build

Key components:

- SUPERflex™-12 pipe
- UltraSlim™-15
- Manifold and water controls
- Thermostats and wiring centres



Heat output

150mm pipe centres 50W/m² to 65W/m²

*Outputs shown are approximate, depending on room temperature and floor covering. This range typically delivers the flow temperature with a plywood coverboard and 1 tog floor covering. Based on a flow temperature of 45°C to 50°C.



About us

No ifs, no buts. The award-winning Continal® service means you get an underfloor heating system delivered to you on time, on site, every time, no compromise.