



TileFix®-18 / TileFix®-25 system

TileFix® – The only system you can tile directly onto, with a low-profile from just 18mm.

TileFix® fast-response, high compressive strength system, is ideal for renovation, new build, whole house and single room projects. Designed to accept direct tiling with a standard tile adhesive and is typically installed over existing solid or timber deck floors.

The system is designed to accept ceramic, porcelain, marble and stone tiles, using a suitable tile adhesive. The universal TileFix® panels provide pipe routing for return loops and distribution, ensuring simple installation.

Key system characteristics:

- Overfloor system suitable for any floor construction
- Ultra-high compressive strength panel
- Insulative composite panel for direct tiling
- Low-profile system
- Quick response
- High-performance system
- Universal panel for simple installation
- 18mm and 25mm variants

System options:

The TileFix® system is available in 2 thicknesses

- TileFix®-18: For 12mm pipes at either 100mm or 150mm (Typically used in smaller areas or where minimal floor height build is required)
- TileFix®-25: For 16mm pipes at either 150mm or 200mm (Typically used for larger and whole-house areas)




For:

- Ultra-low profile build up
- Tiling direct using suitable flexible adhesive
- Renovation or new build
- 100mm or 150mm pipe centres

Key components:

- TileFix®-18 or TileFix®-25 composite panels
- · UL80 adhesive
- SUPERflex™-12 pipe (18mm panels)
- SUPERflex[™]-16 / AluPlas[®]-16 pipe (25mm panels)
- Manifold and water controls
- Thermostats and wiring centres



Heat output range TileFix®-18	· ·
100mm pipe centres	70W/m ² to 85W/m ²
150mm pipe centres	60W/m ² to 75W/m ²

Heat output range TileFix®-25	
150mm pipe centres	60W/m ² to 75W/m ²
200mm pipe centres	55W/m ² to 65W/m ²

 $^{\star}\text{Outputs}$ shown are approximate, depending on room temperature and floor covering. This range typically delivers the flow temperature with a tile floor covering. Based on a flow temperature of 45°C to 50°C.















About us

No ifs, no buts. The award-winning Continal® service means you get an underfloor heating system delivered to you on time, on site, every time, no compromise.